

Wheel Kit Installation Guide

For
GENTRON portable generators only.

Step1: What's included



1. 2 Wheels
2. Wheel Axel
3. 2 Large U-Shaped Brackets
4. 2 Rubber Feet
5. 2 Narrow Axel Brackets
6. 10 Large Washers
7. 10 Nuts
8. 8 Small Washers
9. 4 Pins
10. 7 Small Bolts
11. 2 Large Bolts

Foot Assembly (Before)



Parts Required: 1 Large U-Shaped Bracket (Part 3)
1 Large Screw (Part 11)
1 Rubber Foot (Part 4)
1 Nut (Part 7)

(After)



Attaching the Feet



Attach the feet to the appropriate holes in the frame. (See Page 5)



Use 2 small bolts (Part 10)
2 large washer (Part 6)
2 Nuts (Part 7)

Follow the same steps above to install the second foot.

Wheel Installation



- Parts Required: 1 Axle Bracket (Part 5)
2 small bolts
2 small washers
2 large washers
2 nuts

Attach the axel brackets to the appropriate holes in the frame.



Follow the above steps to install the second axel bracket.



Once both axle brackets are installed, slide the axle bar in.





Insert the pin (part 9) as shown above.



Insert the wheel onto the axel.



Insert the second pin as shown above.